

# AirLink

## Compact industrial WiFi access point



- All-in-one : AP/client/repeater/Mesh/router
- WiFi 802.11a/b/g/n (MIMO 2T2R), radio data rate up to 300 Mbps, 2.4/5 GHz
- Advanced security functions
- Easy to configure : web browser, SNMP V3, WaveManager
- Operating System : WaveOS
- DC power supply input (+9VDC to +48VDC) & PoE 802.3af (from model V2)
- Compact case, wall or DIN Rail mounting
- Multichannel fast roaming (in client mode)



## Introduction

AirLink is a WiFi device designed for industrial, building & factory automation and mobile applications:

- **Compact and practical:** a small footprint, wall or DIN rail mounting options and a wide range of power supply make it extremely easy to integrate into electrical cabinets or in tight spaces and thus ideal for machine manufacturers, OEM...
- **Mobility:** with fast roaming performances (<30 ms) and high resilience to shocks/vibrations, it fits perfectly in AGVs, vehicles (buses)...
- **Reinforcement of the coverage:** it has 2 antennas to work in diversity or in MIMO and thus reinforcing the WiFi coverage and the reliability of your indoor radio communications (IIoT, MtoM, remote access & display...).

AirLink is an all-in-one multifunction product: access point, client, repeater, router & Mesh. It supports any type of Ethernet protocol such as Modbus/TCP, EtherNet/IP, Safe Ethernet, PROFINET... Compliant with IEEE 802.11a/b/g/n WiFi standards (2.4 & 5 GHz), it offers up to 300 Mbps radio data rate.

AirLink integrates the latest security standards (WPA2-Enterprise (Radius), DoS, Firewall...) as well as routing and filtering functions facilitating mass deployments (e.g. machine manufacturers, AGVs, buses...).

## Technical characteristics overview

<b>Ethernet interface</b>	1-port Gigabit Ethernet 10/100/1000 Base TX auto-sensing, auto MDI/MDIX cross-over, RJ45 Ethernet interface
<b>WiFi interface</b>	1 radio IEEE 802.11a/b/g/n, MIMO 2T2R, 2.4 / 5 GHz, ANI (Adaptive Noise Immunity)
<b>WiFi radio data rate</b>	802.11a: 6, 9, 12, 18, 24, 36, 48 and 54 Mbps 802.11b/g: 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48 and 54 Mbps 802.11n: MCS0-7, 2 streams (6.5 to 300 Mbps)
<b>Operating frequencies</b>	ISM : 2.4-2.483 GHz (up to 14 channels) UNII : 5.15-5.25 GHz (up to 4 channels) UNII-2 : 5.25-5.35 GHz (up to 4 channels) UNII-2 ext : 5.470-5.725 GHz (up to 11 channels) UNII-3 : 5.725-5.825 GHz (up to 4 channels) Supports DFS and TPC
<b>Output power</b>	2.4 GHz : up to 23.5 dBm (aggregate) / 5 GHz : up to 21 dBm (aggregate)
<b>Sensitivity max.</b>	2.4 GHz : -94 dBm / 5 GHz : -96 dBm
<b>Radio connectors</b>	2 x RP-SMA
<b>Security</b>	Firewall, DoS, https, MAC filtering, WPA/WPA2-Personal & Enterprise (IEEE 802.1X/RADIUS), WEP, tunnels L2 (GRE), VPN (OpenVPN), SNMP V3, client isolation in AP mode
<b>WiFi modes</b>	Access point, client, MESH (IEEE 802.11s), infrastructure, AD-HOC, fast roaming (less than 30 ms), WMM QoS
<b>Ethernet networking</b>	Frames filtering, bridging, repeater, STP/RSTP, VLAN, DHCP (server & client), DNS relay
<b>Ethernet routing</b>	Multicast (PIM), IP redundancy (VRRP), static routes, NAT router, router
<b>Administration</b>	http, https, SNMP agent (V1, V2C, V3), WaveManager administration software
<b>LEDs Signaling</b>	Radio : activity - status   Ethernet : link 10/100/1000 - activity   Power : on-off
<b>Power supply</b>	+9VDC to +48VDC, 3-pin Phoenix connector & PoE Powered Device 802.3af (from model V2)
<b>Consumption</b>	IDLE mode : 1.7 W / Maximum average : 5.8 W / Recommended power supply : 7 W
<b>Dimensions &amp; weight</b>	Compact case L : 103 x l : 67 x h : 24 mm, weight 225 g
<b>Standards and certifications</b>	CE (RED) Safety : EN 62368-1:2014+A11, EN62311 EMC : EN301-489-1, EN301-489-17 Radio : EN 300 328 2.1.1 (2.4 GHz), EN 301 893 2.1.1 (5 GHz, DFS) FCC Radio : FCC ID Z9W-RMB Environmental Shocks and vibration : EN 61373 (CAT 1 CLASS B)
<b>Environment</b>	IP30 Operating temperature: -20°C to +60°C , storage: -40°C à +85°C, humidity: 0% to 99% (non-condensing)
<b>Warranty</b>	5 years

## Ordering references

AirLink	WiFi access point, client, repeater (WDS) and MESH point (IEEE 802.11 a/b/g/n), 10/100/1000 RJ45 Ethernet interface, shipped with two 2.4GHz - 3 dBi / 5GHz - 4 dBi antennas
<b>Accessories :</b>	
PWS12-UNI-PH3	AC (110V / 220V) to 12VDC power adapter with cable terminated by a 3-pin Phoenix terminal block
WL-FIX-RD2	Din rail fixing kit

All the brand names mentioned in this document are trademarks. ACKSYS is constantly looking at ways to improve its products. The current specifications may therefore be modified without notice and the characteristics set out herein should not be construed as creating any contractual obligation. All the products featured herein are designed and manufactured in Europe.

Pneutrol International Limited

sales@pneutrol.com