

SPECIFICATION


FLUID	: Air filtered, lubricated or not
PORTS	: Instant fittings for flexible tube Ø 4 mm OD
PRESSURE	: 0 to 8 bar
TEMPERATURE	: - 5°C to + 50°C
OPERATORS	: Mechanical
FLOW (Qv at 6 bar)	: 140 l/min (ANR)
Ø NOMINAL	: 2,5 mm

CONSTRUCTION

Spool and poppet design closed centre
Body zinc diecasting
Internal parts in stainless steel and elastomer
Instant fittings in brass
Sealing Nitrile (NBR)
Built-in silencer



CHOICE OF EQUIPMENT

FUNCTION NC Normally closed		 Mechanical operator			1 = Pressure 2 = Outlet 3 = Exhaust (not tapped)
Operating head + body		Effort (daN) Supply pressure			CODES
Type	Description	2 bar	5 bar	8 bar	
	Simple push	1	1,7	2,5	30900002
	Lever roller plastic roller	0,5	0,9	1,3	30900003
	Lever roller ball bearing roller	0,5	0,9	1,3	30900001
	1 way trip plastic roller (Life : 1 million cycles)	0,5	0,9	1,3	30900004
	Threaded head push (*)	1	1,7	2,5	30900006

(*) The pilot valve with a threaded head, is equipped with a treated steel stop rig which allows the valve to be used as an end stop (max. force 200 kg, dia. 50 mm cylinder).

