

Product Datasheet

Codeflat Industrial Layflat Hose

LH & LHM Series





It is a general purpose hose and is especially suitable for drainage of locations with relatively small differences in elevation; for temporary water supply: for sprinkler irrigation or due to its resistance to most chemicals, for spreading liquid fertilizers and agricultural chemicals.

Colour: Blue. Operating temperature -25oc / +60oc.

Medium Duty, Yellow Layflat - LHM series

Medium pressure, flat hose made of plasticized PVC and reinforced with polyester yarns. For conveyance of water, other liquids or fertilisers. Also suitable for irrigation systems, sprinklers and water supply.

Colour: Yellow. Operating temperature -25oc / +60oc.

KEY FEATURES:

- Compact in design.
- Made from Cadmium free materials.
- Resistant to a wide range of chemicals.
- Silicone-free.
- Good resistance to abrasion.
- Provides good flexibility.
- Operating temperature -25oc to +60oc.



- Minimum electrical conductivity.
- Tough and durability for longer lifespan.
- Fast liquid transfer.
- Nominal 3 Bar working pressure (Light duty).
- Nominal 6 Bar working pressure (Medium duty).

SIZES:

- Available in 100m coils
- | 25mm to 207mm ID

COLOURS: ()



- | Blue (Light Duty)
- Yellow (Medium Duty)

APPLICATION EXAMPLES:

Suitable for drainage, water supply, irrigation and sprinkler systems.

Can also be used for chemical transfer such as liquid fertilisers and other agricultural chemicals.

	LH497	LH498	LH499	LH500	LH501	LH502	LH503	LH504
Ex Stock	n/a							
Inner Diameter	25mm	32mm	40mm	52mm	65mm	77mm	103mm	153mm
Tube Material	PVC							
Length	100m Coils							
Maximum Working Pressure	3 Bar							
Working Temperature	-25°C to +60°C							
Weight per meter	n/a	220g	220g	280g	300g	450g	650g	1kg
Weight per coil	n/a	22kg	22kg	28kg	30kg	45kg	65kg	100kg