# Ethernet Adapter

product information sheet

DIN rail mounted Ethernet adapter for easy networking of multiple sensors



**Pneutrol International Limited** 

UK Office 5 Caulside Drive, Antrim, BT41 2DU United Kingdom TEL: +44 (0) 28 9448 1800 www.concretespares.co.uk



sales@pneutrol.com

European Office Unit 6, Saint Anthony's Business Park, Ballymount Road, D22 VW95 Ireland TEL: +353 (0) 1 4373653 www.concretespares.ie

# **Technical information**

# **KEY FEATURES**

# **Networking**

Compatible with networks using DHCP or fixed IP addresses

Sensors: Network up to 16 sensors via standard Ethernet connection reducing cabling costs. Allows full access to all sensor parameters for remote diagnostics and configuration

**Controls:** Ethernet connection to Hydro-Control V enabling remote recipe selection, reporting and support

# **Power Over Ethernet (Optional)**

Remotely power sensors and controls over an Ethernet cable eliminating the requirement for a local DC power supply

# **Remote Connection**

Use to configure and troubleshoot via the internet

# Compact

Small footprint which fits industry standard DIN rail

# **User Friendly**

Easy to install and use – no special cables or software required

# **OPTIONS**

# **Ethernet Adapter Kit – EAK01:**

EA01: Ethernet Adapter

Ethernet Patch cable (0.5m)

# **Ethernet Power Kit – EPK01:**

EA01: Ethernet Adapter

EPA01: Ethernet Power Adapter

**EPI01: Ethernet Power Injector** 

3 x Ethernet Patch cables (0.5m)

**IEC Mains Cable** 

# **Connections**

EA01: Ethernet RJ45 10 Base T or 100 Base TX (Auto Sensing) 24V power / RS485 / RS232 via

screw terminals

EPA01: Ethernet in/out

24V DC out via screw terminals

EPI01: Ethernet RJ45 100 base T in/out IEC mains inlet (cable supplied)

### Construction

Plastic DIN rail mountable box to IP30 for installation in wiring junction box

### Fixing

DIN rail (DIN 46277-3)

# **Power Supply**

EA01: 24V DC 30W (when used without EPA01)

Power Injector EPI01 (supplied with EPK01): 100-240 VAC

# **Operating Temperature**

0-70°C

# **Dimensions**

EA01: 70mm (w) x 86mm (h) x 57mm (d) EPA01: 35mm (w) x 86mm (h) x 57mm (d) EPI01: 65mm (w) x 140mm (h) x 36mm (d)

Note: please allow space for cables to be fitted



UK Office 5 Caulside Drive, Antrim, BT41 2DU United Kingdom TEL: +44 (0) 28 9448 1800 www.concretespares.co.uk

European Office

Unit 6, Saint Anthony's Business Park, Ballymount Road, D22 VW95 Ireland

TEL: +353 (0) 1 4373653 www.concretespares.ie

Pneutrol International Limited

